

PILING HAMMERS

DH-35

FEATURES

- Hydraulic, double-acting impact hammer.
- Excavator, MOVAX multi-tool piling leader, piling rig or crane mounted.
- Excavator mounted
 - incorporates a 1.3 m leader
 - mounting with pin adapter (tilt +/-15°, no rotation)
- MOVAX multi-tool piling leader mounted
 - incorporates a 1.3 m leader
- Available with drive caps for a range of different pile sections.
- Controlled with the MOVAX Control System (MCS™)
- Available with the MOVAX Information Management System (MIMS™)



TECHNICAL DATA

		Excavator mounted	Excavator leader-mounted	Piling rig mounted	Crane mounted
Total weight (excl. adapter) *	kg	5750	4900**	4900**	4900**
Ram weight	kg	3100	3100	3100	3100
Blows per minute	1/min	0-100	0-100	0-100	0-100
Impact energy	kNm	0-35	0-35	0-35	0-35
Drop height	m	0-1,2	0-1,2	0-1,2	0-1,2
Pressure relief set max	bar	350	350	350	350
Operating pressure	bar	250	250	250	250
Oil flow rate	l/min	120	120	120	120
Tilt angle	°	+/-15	N/A	N/A	N/A
Total height	mm	4460	4460	4610	4610
Frame width	mm	650	650	650	650
Transport width	mm	1200	1200	1200	1200
Transport depth	mm	1870	1870	1870	1870
Excavator class					
Excavator mounted	t	(33) 35-50	35-50	-	-

* including tilt device

** excluding leader adapter